

LDAP

LDAP en UNIFACE

LDAP

- The Lightweight Directory Access Protocol (LDAP)
- Hulp tool
- Asn file
- Nu in Uniface
- Trial en error
- Oplossing
- Code!

Hulp tool

- JXplorer (Gratis!!)

The screenshot shows the 'Open LDAP/DSML Connection' dialog box. It contains the following fields and options:

- Host: 10.50.5.40
- Port: 389
- Protocol: LDAP v2
- DSML Service: (empty)
- Optional Values: Base DN: OU=Groepen,OU=Accounts,OU=AGIS,DC=agisweb,DC=LOCAL
- Security: Level: User + Password; User DN: koldijk, paul; Password: *****
- Use a Template: Save, LDAP Gebruiker, Delete, Default
- Buttons: OK, Cancel, Help

The screenshot shows the JXplorer Java web interface. The main content area displays the JXplorer logo and the text: "Welcome to JXplorer Java". Below this, it states: "This panel will display the results of your directory browsing and searches. If you need any assistance, use the help option on the menu bar above." A smaller version of the 'Open LDAP/DSML Connection' dialog box is overlaid on the page, showing the same configuration as the first screenshot. The status bar at the bottom indicates "Not Connected".

De ASN file

- LDAP driver
- PATHS
- ENTITIES

```
H:\Paul\Project\Test9302\Asn\Test9302.asn *
1 [SETTINGS]
2 $SEARCH_OBJECT DBMS_FIRST
3 $SEARCH_DESCRIPTOR DBMS_FIRST
4 $LICENSE_OPTIONS 7188@srv-app07
5 $LANGUAGE USA
6 $PUTMESS_LOGFILE ..\LOG\ONTW.LOG
7
8 [DRIVER_SETTINGS]
9 SOL U3.4
10 SEQ U1.0
11 LDP U1.0
12 USYS$LDP_PARAMS addbase:off
13
14 [PATHS]
15 $SOL SOL:Shmem Solid:|dba|dba
16 $LDP LDP:10.50.5.40:OU=Accounts,OU=AGIS,DC=agisweb,DC=LOCAL|Koldijk, Paul ██████████
17
18 $DEF $SOL
19 $UUU $SOL
20 $IDF $SOL
21 $SYS $SOL
22
23 [ENTITIES]
24 GEbruiker.LDAP $LDP:GEbruiker@OU=Gebbruikers,OU=Accounts,OU=AGIS,DC=agisweb,DC=LOCAL
25 GROEP.LDAP $LDP:GROEP@OU=Groepen,OU=Accounts,OU=AGIS,DC=agisweb,DC=LOCAL
26 *.LDAP $LDP:*. *
27
28
```



Nu in Uniface...

- Probleem met 'multiple value' veld
- Max 255 lang?

Data Storage and Retrieval on LDAP

LDAP differs substantially in structure from traditional relational databases.

Consider the following factors when retrieving or writing data to an LDAP server:

- Only fixed-length string data can be accessed via the LDAP connector. Variable-length data, or strings longer than 255 characters, are truncated to a length of 255 characters. Binary data cannot be accessed.
- The LDAP connector does not support overflow tables, so fields must not be formatted as C* or R*.
- LDAP does not support entity names. A Uniface entity is no more than a grouping of fields to LDAP. It is always necessary to specify a retrieve profile that limits the amount of data retrieved. See [Map LDAP Entries to Uniface Entities](#)



Hoe opgelost?

- Trial en error
- 8189

```
[Inactive idf Transcript]
File
Fatal error: 8035 - Fixed part of table '' exceeds DBMS () limits.

*finished*
```

Define Entity: LDAP

Entity Name	Description	Modified
ALG_G_DATAGIS	Globale Groep Datagis med	16-mar-11 08:28:29
GEBRUIKER	Gebruiker	16-mar-11 09:49:22
GROEP	Groepen	16-mar-11 08:28:29
LDAP_DATA	1e Level	16-mar-11 08:28:29

Details of 'ALG_G_DATAGIS'

Entity Abbreviation: ALG_G_DATAGIS

Occurrence Interface Name: ALG_G_DATAGISOCC

Collection Interface Name: ALG_G_DATAGISCOLL

Business Object

Default Data Access: DBMS Path: LDAP (LDP)

Entity Service Name: []

Number of Occurrences: Minimum [], Maximum []

Locking: Optimistic, Cautious, No Updates

Option: Border

Interface: Shorthand [C*]

Widget Type: None

Pop-up Menu: []

Comments: []

Fields... Keys... Relationships... Triggers... OK Cancel

Define Field: GEBRUIKER.LDAP

Field Name	Description	Label	Modified
CN			04-apr-11 16:29:36
DISPLAYNAME			04-apr-11 16:29:36
DISTINGUISNAME			16-mar-11 10:20:26
MAIL			04-apr-11 16:29:36
NAME			04-apr-11 16:29:36
SAMACCOUNTNAME			04-apr-11 16:29:36
MEMBEROF			04-apr-11 16:36:03

Details of 'MEMBEROF'

Widget Type: EditText

HTML Control: Text

Initial Value: []

Interface: Shorthand [C7872]

Syntax: Template

Layout: Template

Pop-up Menu: []

Characteristics: Database [String]


For Technical use only

Comments: []

Triggers... OK Cancel

Code!


- `clear`
`$Groep$ = ".*Afdeling.*"`
`Retrieve`
- `read u_where`
`(samaccountname=$Groep$)`



The screenshot shows a window titled 'MEMBEROF' with a table of members. The table has two columns: 'volgnr' and 'Groep'. The data is as follows:

volgnr	Groep
1	Bos\
2	Tournet\
3	Schurink\
4	Özbek\
5	Nizamoeddin\
6	Limon\
7	Laseur-de Groot\
8	Ingen\
9	Heijkoop\
10	Burgwal\
11	Bredewoud\

At the bottom of the window, there is a button labeled 'Member'.



The screenshot shows a window titled 'GROUP' with a table of groups. The table has four columns: 'CN', 'DESCRIPTION', 'MEMBER', and 'SAMACCOUNTNAME'. The data is as follows:

	CN	DESCRIPTION	MEMBER	SAMACCOUNTNAME
1	Afdeling Buitenland GBN	Buitenland GBN	CN=Bos\, Hinke,OU=Gebruikers,OU=Accounts,OU=AGIS,DC=agis\	Afdeling Butte-4
2	BV MT		CN=Krijpstra\, Henk,OU=Gebruikers,OU=Accounts,OU=AGIS,DC=agis\	BV Afdelingsmanagement
3	Crediteurenafdeling Agis	20091204; JC; WO 140494	CN=Ommeren\, Yvonne van,OU=Gebruikers,OU=Accounts,OU=AGIS,DC=agis\	Crediteurenafdeling Agis
4	P&A Afdelingssecretariaat	P&A Afdelingssecretariaat	CN=Havekotte\, Annemieke,OU=Gebruikers,OU=Accounts,OU=AGIS,DC=agis\	PA Afdelingssecretariaat
5	AWBZ afdeling Care		CN=Snoek-Taalt\, Grada,OU=Gebruikers,OU=Accounts,OU=AGIS,DC=agis\	Zorg afdeling Care
6	GG-SW-Porthos-Afdelingsmanager Kik		CN=Beijlouw\, Willem,OU=Gebruikers,OU=Accounts,OU=AGIS,DC=agis\	GG-SW-Porthos-Afdelingsmanager Kik
7	GG-PF-Porthos-Mut-Afdeling		CN=GG-SW-Porthos-Functioneel Applicatiebeheerder,OU=Gebruikers,OU=Accounts,OU=AGIS,DC=agis\	GG-PF-Porthos-Mut-Afdeling
8	BV Afdelingsmanagers en Teamleiders		CN=Veenen\, Susan van,OU=Gebruikers,OU=Accounts,OU=AGIS,DC=agis\	BV Afdelingsmanagers en Teamleiders
9	#Afdeling Buitenland Secretariaat	call 259683		Afdeling Buitenland

At the bottom of the window, there is a button labeled 'Members'.